

CS PM 600 - Mobile current/effective power meter suitable for: DS 500 mobile / DS 400 mobile / PI 500

Measures voltage, current and calculates:

Effective power [kW] [kVA] Apparent power Reactive power [kVar] Active energy [kWh] cos phi



Magnetic voltage measuring tips electrically isolated



Special features:

- Magnetic voltage measuring tips for picking off the voltage during operation
- Hinged current transformers encompass the conductors of the phases L1, L2, L3. This can also be done during operation

All measured data are transferred digitally (Modbus) to DS 500 mobile/ DS 400 mobile and can be recorded there.



Example: Measurement on the compressor

TECHNICAL DATA CS PM 600

Parameters: Voltage (Volt)

Current (Ampere)

Cos phi

Effective power (kW) Apparent power (kVA) Reactive power (kVar) Active energy (kWh) Power frequency (Hz) All parameters are transferred digitally to DS 500 mobile /DS 400 mobile

Accuracy current measurement:

Threshold values for current deviation. Loss angle according to IEC 60044-1. Current deviation in % at

rated current in 120% 100% 1.5 20% 3 5%

Accuracy active energy:

IEC 62053-21 Class 1

Sensor connec-3 x current transformers tions:

(L1,L2,L3,N)

4 x voltage measurement